

NOTES:

CURRENT RATING: 1A AC/DC
 VOLTAGE RATING: 100V AC/DC
 TEMPERATURE RANGE: -25°C~+85°C
 CONTACT RESISTANCE: 20mΩ MAX
 INSULATION RESISTANCE: 1000MΩ MIN
 WITHSTANDING VOLTAGE: 800V AC/MINUTE
 FLASH: 0.05MAX; WARPAGE: 0.08MAX

A1001 W VS - 2*NP X - X X - X X - NK-HF

W: 示意针座
 后无0默认材质为V0
 后带2示意V2
 VS: V示意180°直针, VS立式
 R示意90°弯针, RS卧式
 NP: 1为PPS, 2为PBT, 3为LCP, 4为ABS, 5为PA6T, 6为PA66
 X: 1为直插, 2为贴片, 3为插针, 4为插针, 5为插针, 6为插针
 NK: 1为直插, 2为贴片, 3为插针, 4为插针, 5为插针, 6为插针
 HF: 1为直插, 2为贴片, 3为插针, 4为插针, 5为插针, 6为插针

Circuit No.	Dimensions		
	A	B	C
08P	3.0	6.3	4.4
10P	4.0	7.3	5.4
12P	5.0	8.3	6.4
14P	6.0	9.3	7.4
16P	7.0	10.3	8.4
18P	8.0	11.3	9.4
20P	9.0	12.3	10.4
24P	11.0	14.3	12.4
28P	13.0	16.3	14.4
30P	14.0	17.3	15.4
34P	16.0	19.3	17.4
40P	19.0	22.3	20.4
50P	24.0	27.3	25.4
60P	29.0	32.3	30.4

东莞市平达电子科技有限公司

料号PART NO: EST1001WVS-2*NPX-X2

品名 TITLE: SH1.0立式双排(有柱)

一般公差
 GENERAL TOLERANCE
 X.X ±0.30
 X.XX ±0.25
 X.XXX ±0.10
 ANGLE ±1°

材料: 单位: MM 包装规格: 比例: 1:1
 制图: 胡宗显 审核: 核准: 日期: 2022/04/21

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY

NO.	DESCRIPTION	Q'TY.	MATERIAL
3	FITTING NAIL	2	BRASS
2	TERMINAL	~	BRASS
1	HOUSING	1	THERMAL PLASTIC, UL94-V0

