





**A1005 T P X - 2 X - X**

代码+间距  
T示意端子  
X公端  
G母端  
X普通 C示意90°  
L长 S示意180°  
0素材  
2镀锡先冲后镀  
3镀锡先镀后冲  
X普通脚  
H高脚  
P磷铜  
B黄铜  
E合金铜

- Notes:
1. Material: Phosphor bronze, T=0.12;
  2. Finish: Nickel 20U" min Over all.  
Tin 80U" minm over nickel.
  3. Applicable Wire range: AWG#28~#32
  4. Insulation O. D. : 0.8mm (Max);
  5. Current Rating: 1A AC, DC;
  6. Vovtage RATING: 50V AC/DC;
  7. Temperature rang: -25℃~+85℃;
  8. Contact resistance: 20 MΩ Max;
  9. Insulation Resistance: 100 mΩ Min;
  10. Withstanding voltage: 500V AC/minute;
  11. Packin Qty: 2000PCS/Reel;

东莞市平达电子科技有限公司



				料号PART NO: A1005TPX-2X-G		一般公差 GENERAL TOLERANCE	
				品名 TITLE: NH1.0-T		X.X ±0.25	
				材料: C5191	单位: MM	包装规格:	X.XX ±0.20
				制图:	审核:	比例: 1:1	ANGLE ±1°
日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY	制图:	审核:	日期: 2021.3.9	