

**A0500 W VS - 1\*NP X - X - X X - NK-HF**



代码-颜色      PIN数      X本色      X普通      D防呆型      G为PIN针镀金      HF无卤  
 1单排      2双排      B黑色      B带扣      2示意有柱      S为PIN针镀锡      NF普通含卤  
 U超薄      3示意无柱      NR为NO MARK      MK为有MARK  
 PH组合排针      FH组合排母      H高弯      P平弯

V示意180°直针, VS立式  
 R示意90°弯针, RS卧式



W示意针座  
 W后无0默认材质为V0  
 W后带2示意V2

1为PPS, 2为PBT, 3为LCP, 4为ABS, 5为PA6T, 6为PA66

CKTS	DIM A	DIM B	DIM C
4	1.50	2.60	6.40
5	2.00	3.10	6.90
6	2.50	3.60	7.40
7	3.00	4.10	7.90
8	3.50	4.60	8.40
9	4.00	5.10	8.90
10	4.50	5.60	9.40
11	5.00	6.10	9.90
12	5.50	6.60	10.40
13	6.00	7.10	10.90
14	6.50	7.60	11.40
15	7.00	8.10	11.90
16	7.50	8.60	12.40
17	8.00	9.10	12.90
18	8.50	9.60	13.40
19	9.00	9.10	13.90
20	9.50	10.60	14.40
21	10.00	11.10	14.90
22	10.50	11.60	15.40
23	11.00	12.10	15.90
24	11.50	12.60	16.40
25	12.00	13.10	16.90
26	12.50	13.60	17.40
27	13.00	14.10	17.90
28	13.50	14.60	18.40
29	14.00	15.10	18.90
30	14.50	15.60	19.40
31	15.00	16.10	19.90
32	15.50	16.60	20.40
33	16.00	17.10	20.90
34	16.50	17.60	21.40
35	17.00	18.10	21.90
36	17.50	18.60	22.40
37	18.00	19.10	22.90
38	18.50	19.60	23.40
39	19.00	20.10	23.90
40	19.50	20.60	24.40
41	20.00	21.10	24.90
42	20.50	21.60	25.40
43	21.00	22.10	25.90
44	21.50	22.60	26.40
45	22.00	23.10	26.90
46	22.50	23.60	27.40
47	23.00	24.10	27.90
48	23.50	24.60	28.40
49	24.00	25.10	28.90
50	24.50	25.60	29.40
51	25.00	26.10	29.90
52	25.50	26.60	30.40
53	26.00	27.10	30.90
54	26.50	27.60	31.40
55	27.00	28.10	31.90
56	27.50	28.60	32.40
57	28.00	29.10	32.90
58	28.50	29.60	33.40
59	29.00	30.10	33.90
60	29.50	30.60	34.40



锁条	LCP	黑色	1
焊片	C5191	镀锡	2
端子	C5191	镀锡	1
基座	LCP	本色	1
名称	材料	表面状态	数量
PART NAME	MATERIAL	FINISHING	QTY.



- Note:
- Material:
    - Housing: thermoplastic high temp.UL94V-0; Color: natural.
    - Latch: thermoplastic high temp.UL94V-0; Color: black.
    - Terminal: copper alloy.
    - Fitting Nail: copper alloy.
  - Finsh:
    - Terminal: Underplating: Au/matt Tin overall.
    - Fitting Nail: Underplating: matt Tin overall.
  - Product must comply HF RoHS specification.

## 东莞市平达电子科技有限公司

			料号PART NO: A0500WRS-1*NPX-X		一般公差 GENERAL TOLERANCE	
			品名 TITLE: 0.5-Wafer(贴片欣盖)		X.X ±0.25	
			材料:		X.XX ±0.20	
			单位: MM		ANGLE ±1°	
			包装规格:		比例: 1:1	
			比例: 1:1		日期: 2022.6.13	
日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY	制图:	审核:	核准:

