



A1250 H - 1*NP X - K - X - HF-NK - X

代码+间距 PIN数
 1示意单排
 2示意双排

X普通
 B带扣
 C刺破
 L示意LOCK TYPE
 U超薄F防呆型
 HV带高凸点
 LC带低凸点
 K卡槽
 E有耳
 NE无耳

X公胶壳
 G母胶壳

NO MARK

HF示意无卤
 NF普通含卤

A灼热丝750
 B灼热丝850
 X普通料

Poles	Dimensions		
	A	B	
2	1.25	2.95	3.00
3	2.50	4.20	4.25
4	3.75	5.45	5.50
5	5.00	6.70	6.75
6	6.25	7.95	8.00
7	7.50	9.20	9.25
8	8.75	9.00	10.50
9	10.00	10.45	11.75
10	11.25	11.70	13.00
11	12.50	12.95	14.25
12	13.75	14.20	15.50
13	15.00	15.45	16.75
14	16.25	16.70	18.00
15	17.50	17.95	19.25
16	18.75	19.20	20.50

- Applicable Wire Range: AWG#28~#32
- Insulation O.D.: 0.80mm (Max.)
- Current Rating: 2A AC,DC
- Voltage Rating: 125V AC,DC
- Temperature Rang: -25°C~+85°C
- Contact Resistance: 20mΩ Max
- Insulation Resistance: 100MΩ Min
- Withstanding Voltage: 500V AC/minute

东莞市平达电子科技有限公司

				料号PART NO: A1250H-1*NPX-K-X 品				一般公差 GENERAL TOLERANCE	
				名 TITLE: MX1.25-H(有槽)				X.X ±0.30	
材料: PA66 94-V0		单位: MM		包装规格: 1K/包		比例: 1:1		X.XX ±0.25	
日期版次 REVISION		日期 DATE		变更内容 DESCRIPTION		核 准 APPROVALBY		X.XXX ±0.15	
						制图:		审核:	
						日期: 2022/04/03		核 准:	
								核 准:	

