



Part No	A	B	C
2	1.25	4.40	3.10
3	2.50	5.65	4.35
4	3.75	6.90	5.60
5	5.00	8.15	6.85
6	6.25	9.60	8.10
7	7.50	10.65	9.35
8	8.75	11.90	10.60
9	10.00	13.15	11.85
10	11.25	14.40	13.10
11	12.50	15.65	14.35
12	13.75	16.90	15.60
13	15.00	18.15	16.85
14	16.25	19.40	18.10
15	17.50	20.65	19.35
16	18.75	21.90	20.60

Circuits: 2~16

A1250 H - 1*NP_X - X - X - HF-NK - X

代码+间距 PIN数 X本色
B黑色 X普通 X公胶壳
R红色 B带扣 G母胶壳
L蓝色 C刺破 2L示意两侧带锁扣
Y黄色 U超薄防呆型 HV带高凸点
G绿色 LC带低凸点, K卡槽
C透明 E有耳 NE无耳

H示意胶壳, H后无数字默认材质V0
H后带数字2示意材质V2

NO MARK HF示意无卤 NF普通含卤

A灼热丝750 B灼热丝850 X普通料

■ SPECIFICATIONS

- Voltage rating: 125V AC/DC;
- Current rating: 1A AC/DC;
- Withstanding Voltage: 250V AC/minute
- Insulation resistance: 100MΩ Min
- Temperature range: -40℃~+85℃
- Contact resistance: 20mΩ Max
- Conductor size: AWG28~#32

东莞市平达电子科技有限公司

料号PART NO: A1250H-1*NPX-X-G

品名 TITLE: MX1.25-H(母)

材料:

单位: MM

包装规格:

比例: 1:1

制图:

审核:

核准:

日期: 2022. 4. 14

一般公差
GENERAL TOLERANCE
X.X ±0.30
X.XX ±0.25
ANGLE ±1°

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY

