



- NOTES:
1. Material:C5191
 2. Color:
 3. Corrent Roting:1A AC, DC
 4. Voltage rating:150V AC, DC
 5. Temperature Rang:-25° c~+85° c
 6. Conctoct Resistance:30mΩ Min
 7. Insulation Resistance:500MΩ Min
 8. Withstanding Voltage:500V AC/minute
 9. APPLICABLE WIRE:AWG#28~#32
 10. Q' TY:15000PCS/REEL

A1252 T P X - 2 X - X

↑ 羿通代码+间距
 ↑ T示意端子
 ↑ P磷铜
 ↑ B黄铜
 ↑ E合金铜
 ↑ X普通脚
 ↑ H高脚
 ↑ 0素材
 ↑ 2镀锡先冲后镀
 ↑ 3镀锡先镀后冲
 ↑ 4镀全镍(镀后冲)
 ↑ 4.2镀全镍先冲后镀
 ↑ 5G、15G示意镀金5U"或15U", 1G示意镀金1U"

X公端
 G母端
 C示意90°
 S示意180°

东莞市平达电子科技有限公司

料号PART NO: A1252TPX-2X-G

品名 TITLE: DF13-T

材料: 单位: MM 包装规格: 比例: 1:1
 制图: 审核: 核准: 日期: 2021.11.30

一般公差
 GENERAL TOLERANCE
 X.X ±0.25
 X.XX ±0.20
 ANGLE ±1°

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY

6

5

4

3

2

1