



a-a section




b-b section



c-c section

技术参数: SPECIFICATIONS

- 适用线规: AWG#28~#32  
Applicable wire: AWG#28~#32
- 额定电压: 250V DC/AC (有效值)  
Voltage rating: 250V DC/AC (rms)
- 额定电流: 1.0A  
Current rating: 1.0A
- 耐压值: 800V AC(有效值)  
Withstand voltage: 800V AC(rms)
- 工作温度: -25℃~+85℃  
Working Temperature: -25℃+85℃
- 绝缘电阻: ≥1000MΩ  
Insulation resistance: ≥1000MΩ
- 接触电阻: ≤0.02Ω  
Contact resistance: ≤0.02Ω



d-d section

A1253 T P X - 2 X- X

代码+间距      T示意端子

X普通脚  
H高脚

0素材  
2镀锡先冲后镀  
3镀锡先镀后冲  
5G、15G示意镀金5U"或15U", 1G示意镀金1U"

X公端  
G母端

X普通  
L长  
S短

P磷铜  
B黄铜  
E合金铜

EST1253TPX-2X-X

东莞市平达电子科技有限公司

				料号PART NO: A1253TPX-2X-G				一般公差 GENERAL TOLERANCE	
				品名 TITLE: DF14- T				X.X ±0.15	
				材料: C5191		单位: MM		X.XX ±0.05	
				核 准		包装规格: 5K/卷		ANGLE ±1°	
日期版次 REVISION				日期 DATE		变更内容 DESCRIPTION		核 准 APPROVALBY	
				制图: LI		审核: LI		比例: 1:1	
						核准: LI		日期: 2022/04/16	

6

5

4

3

2

1