



PIN	DIM. (mm)	
	A	B
02	1.25	7.45
03	2.50	8.70
04	3.75	9.95
05	5.00	11.20
06	6.25	12.45
07	7.50	13.70
08	8.75	14.95
09	10.00	16.20
10	11.25	17.45
11	12.50	18.70
12	13.75	19.95
13	15.00	21.20
14	16.25	22.45
15	17.50	23.70
20	23.75	29.95
25	30.00	36.20
30	36.25	42.45

A1253 W VS - 2*NP X - X X - X X - NK-HF

弄通代码+间距 V示意180°直针 VS立式 R示意90°弯针 RS卧式 W示意针座 W后无0默认材质为V0 W后带2示意V2
 PIN数 X本色 B黑色 R红色 L蓝色 Y黄色 G绿色
 1单排 2双排
 X普通 B带扣 U超薄 F组合排母 H高弯 P平弯
 D防呆型 2示意有柱 3示意无柱
 C为PIN针镀金 S为PIN针镀锡 NK为NO MARK MK为有MARK
 1为PPS, 2为PBT, 3为LCP, 4为ABS, 5为PA6T, 6为PA66
 0为无床 NF普通合床

- NOTES:
- Material:
Insulation:Nylon9T,UL94V-0(Beige)
Pin:Brass/Tin 80u" min. over Nickel 20u" min.
Brass/Gold Flash. over Nickel 20u" min.
Tab:Brass/Tin 80u" min. over Nickel 20u" min.
Brass/Gold Flash. over Nickel 20u" min.
 - Current Rating: 1A AC,DC
 - Voltage Rating: 150V AC,DC
 - Temperature Rang: -25°C~+85°C
 - Contact Resistance: 30mΩ Max
 - Insulation Resistance: 500MΩ Min
 - Withstanding Voltage: 500V AC/minute

东莞市平达电子科技有限公司

				料号PART NO: A1253WRS-1*NPX-X				一般公差 GENERAL TOLERANCE	
				品名 TITLE: DF14-wafer贴片				X.X ±0.25	
				材料:		单位: MM		包装规格:	
				比例: 1:1		日期: 2022.4.16		ANGLE ±1°	
日期版次 REVISION		日期 DATE		变更内容 DESCRIPTION		核 准 APPROVALBY		制图:	

6

5

4

3

2

1