

A1255 H - 1\*NP X - B - X - HF-NK - X

代码+间距      PIN数      NO MARK      A灼热丝750      B灼热丝850      X普通料

X普通      X公胶壳      G母胶壳

B带扣      C刺破      2L示意两侧带锁扣      U超薄F防呆型      HV带高凸点      LC带低凸点      K卡槽      E有耳      NE无耳

H示意胶壳, H后无数字默认材质V0, H后带数字2示意材质V2

1示意单排, 2示意双排

Specifications

- (1) Voltage rating: 200V AC/DC
- (2) Corrent rating: 1A AC/DC
- (3) Withstanding voltage: 900V AC/minute
- (4) Temperature range: -25°C ~ +85°C
- (5) Insulation resistance:  $\geq 1000M\Omega$
- (6) Contact resistance:  $\leq 20M\Omega$
- (7) After environmental testing:  $\leq 30M\Omega$

东莞市平达电子科技有限公司


料号PART NO: A1255H-1\*4PX-2L-X

品名 TITLE: MX1.25-H短体超薄(带扣)

材料:LCP      单位: MM      包装规格:      比例: 1:1

日期版次 REVISION      日期 DATE      变更内容 DESCRIPTION      核 准 APPROVALBY      制图:      审核:      核准:      日期: 2022.4.16

一般公差  
GENERAL TOLERANCE  
X.X ±0.30  
X.XX ±0.25  
X.XXX ±0.10  
ANGLE ±1°



6

5

4

3

2

1