



SPECTION

- Current rating: 2A AC, DC (AWG #24)
- Voltage rating: 100V AC, DC
- Temperature range: -25°C to +85°C (including temperature rise in
- Contact resistance: Initial value/30mΩ max.After environmental testing /60mΩ max.
- Insulation resistance: 500M Ω min.
- Withstanding voltage: 500V AC/minute
- Applicable wire: Conductor size/AWG #28 to #24
- Insulation O. D. /0.8 to 1.2mm

Contacts	Dimensions(mm)			
	Dim A	Dim B	Dim C	Dim D
2x05	7.50	6.00	11.20	9.30
2x06	9.00	7.50	12.70	10.80
2x07	10.50	9.00	14.20	12.30
2x08	12.00	10.50	15.70	13.80
2x09	13.50	12.00	17.20	15.30
2x10	15.00	13.50	18.70	16.80
2x13	19.50	17.50	23.20	21.30
2x15	22.50	20.50	26.20	24.30

东莞市平达电子科技有限公司

				料号PART NO: A1502H-2*NPX-B-X				一般公差 GENERAL TOLERANCE	
				品名 TITLE: 1502-H				X. X ±0.30 X. XX ±0.20	
日期版次 REVISION		日期 DATE		变更内容 DESCRIPTION		核 准 APPROVALBY		材料: 单位: MM 包装规格: 比例: 1:1	
								日期: 2022. 4. 16	

